

4KHD5328HC-L

32 Channel 2U 4K&H.265 Network Video Recorder



4K ULTRA HD

HDMI®

HIGH-DEFINITION MULTIMEDIA INTERFACE

- H.265/H.264 code decoding , Support OnVif 2.3
- Up to 20MP (5632x4224) Resolution for Preview and recording
- Network Video Input Bandwidth:256Mbps
- 4K (3840*2160) HDMI output / VGA simultaneous video output
- Support HDMI Spot Output
- Support 4ch Face detection or 8ch Perimeter detection optional
- 16CH alarm in, 4CH alarm out
- Dual 1000M network port
- 2U, 8 SATA (max 48GB), 1 port E-SATA
- The highest 32ch synchronous playback
- Dual 1000M network port
- Two-way voice talk

Specification

Model	4KHD5328HC-L
Memory	4GB DDR3
Operating System	Linux
Video Audio Input	
Voice Talk	1 Channel, BNC port(Line in,2Vpp,1Kohms)
Network Video Input Bandwidth	256Mbps (The highest 32 Channel 1080P@8M)
IPC Input	32 Channel
Video Audio Output	
VGA	1 Channel,1920x1080,1280x1024,1280x720,1024x768 Resolution Optional
HDMI	2
Audio Output	1 Channel,RCA port(Line out,2Vpp,300ohms)
Video And Audio Coding	
Audio Encode	G.711A
Audio Bitrate	64Kbps
Video And Audio Decoding	
IP Channel Resolution	Main Stream: The highest 20M (5632x4224) Sub Stream: Not higher than D1
Video Encode	H.265 (Main Profile@L5.0 High-tie) / H.264 (The highest Profile@Level5.0)
Audio Encode	G.711A,G.726
Multi-channel Playback	The highest 32ch synchronous playback
The Highest Decoding Ability	16 Channel 1080P@30FPS
Intelligent Analysis	
	4 Channel face detection or 8 Channel Perimeter detection optional The highest Support 1080P
Others	
Voice Talk	Two-way voice talk
Motion Detection	Each channel support 396(22x18) detection area; Can be set up multi-level sensitivity ,Necessary to support the IPC
Snapshot	Support JPEG capture
HDD	
SATA Port	8 SATA Port
E-SATA Port	1 Port
Hard Disk	Unlimited hard disk capacity
External Interface	
Network Port	2 RJ45 Ethernet port, 10M/100M/1000M suitable
USB Port	2 USB2.0 port
RS-232	1 Channel
RS-485	1 Channel
Alarm Input & Output	
Alarm Input	16 Channel
Alarm Output	4 Channel
Structure	
Dimensions	2U, 441mmx448mmx88mm (17.36" x 17.64" x 3.47")
Weight	7.0kg (15.43 lb) (without HDD)
Installation	Rack installation, Desktop installation
Electrical Performance	
Power	110V~220V±10% 47Hz~63Hz
Operation Temperature	0°C ~ +55°C (+32°F ~ +131°F)
Operation humidity	10%--90%
Power supply	20W (Without HDD)

OWLTECH SECURITY, INC.

E-mail: sales@owltechcctv.com
www.owltechcctv.com

*Design and specifications are subject to change without notice
@2016 OWLTECH SECURITY, INC.